



## Technical Data Sheet

### FEATURES:

- Valve Action markers allow control of paint flow while keeping the paint in the barrel from drying-out when the cap is off.
- Water-Based markers contain minimal solvents, are non-flammable, and emit no air pollution or harsh chemical odor.
- Unregulated for all modes of shipping, including air.
- Replaceable tips extend the life of your markers.
- Clearly marks on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Available in 6 weather & fade resistant colors.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.

### COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

### HEALTH & SAFETY:

- Avoid skin and eye contact and ingestion.
- For complete health & safety data, refer to SDS at [www.diagraphmsp.com](http://www.diagraphmsp.com)

### DIRECTIONS FOR USE:

- Shake marker well with the cap on
- Twist the cap off
- Gently pump until the tip is primed

### TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/3oz (~11 cc)
- Barrel Size: .625" Diameter x 4" Long

### PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	Halogens	Flash Point	Resistant to	Approx. Dry Time
White	0975000	1.302	24 ppm	> 200°F	550°F	60 Sec
Yellow	0975001	1.299	*	> 200°F	550°F	60 Sec
Black	0975002	1.059	36 ppm	> 200°F	600°F	60 Sec
Red	0975003	1.148	*	> 200°F	700°F	60 Sec
Blue	0975004	1.273	*	> 200°F	550°F	60 Sec
Green	0975005	1.246	*	> 200°F	700°F	60 Sec

\* Test results not available at this time