

Technical Data Sheet

LOW HALOGENS · XYLENE-FREE · ASSEMBLED IN THE USA

GP-X CLASSIC

**VALVE
ACTION**

**ALL
PURPOSE
PAINT
MARKER**

FEATURES:

- Replaceable tips extend the life of your markers.
- Clearly marks on dark or light surfaces.
- Available in 13 weather & fade resistant colors.
- Valve Action markers allow control of paint flow while keeping the paint in the barrel from drying-out when the cap is off.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.
- Black and White meet nuclear specs RDT-F7-3T, rev. 5.1
- Minimum of 60% renewable content.
- No hazardous air pollutants.

COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

DIRECTIONS FOR USE:

- Shake marker well with the cap on
- Twist the cap off
- Gently pump until the tip is primed

TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz (~12 cc)
- Barrel Size: .563" Diameter x 4.75" Long

HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- No Reportable Prop 65
- Flash Point: 62°F (17°C)
- For complete health & safety data, refer to SDS at www.diagraphmsp.com

PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	VOC Level	Total Halogens	Approx. Dry Time
White	0960500	1.22	5.6 lbs/gal	< 57 ppm	20-30 Sec
Yellow	0960501	1.22	6.3 lbs/gal	126 ppm	20-30 Sec
Black	0960502	0.96	5.3 lbs/gal	< 64 ppm	20-30 Sec
Blue	0960503	1.03	7.0 lbs/gal	< 24 ppm	20-30 Sec
Red	0960504	1.02	5.6 lbs/gal	< 200 ppm	20-30 Sec
Green	0960505	1.14	6.5 lbs/gal	42 ppm	20-30 Sec
Pink	0960506	1.19	5.4 lbs/gal	< 200 ppm	20-30 Sec
Gold	0960507	1.01	6.0 lbs/gal	< 200 ppm	20-30 Sec
Brown	0960508	1.02	6.3 lbs/gal	39 ppm	20-30 Sec
Light Green	0960509	1.21	5.9 lbs/gal	53 ppm	20-30 Sec
Orange	0960510	1.01	6.0 lbs/gal	43 ppm	20-30 Sec
Purple	0960511	1.17	5.8 lbs/gal	73 ppm	20-30 Sec
Silver	0960512	0.95	5.2 lbs/gal	< 200 ppm	20-30 Sec