



Technical Data Sheet



Xylene-free

FEATURES:

- A bigger, bolder, wider version of the industry favorite GP-X Classic.
- Valve Action markers allow more control over ink flow and keep the ink in the barrel from drying out if the cap is left off.
- Replaceable tips extend the life of your markers.
- Opaque paint markers will clearly mark on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Available in 6 weather & fade resistant colors.
- Sold by color in boxes of 3. Cartons include 12 boxes / 36 markers.
- Black and White meet nuclear specs RDT-F7-3T, rev. 5.1
- Minimum of 60% renewable content.
- No hazardous air pollutants.

COMPATIBILITY:

- Safe for most porous & non-porous surfaces
- Test on surfaces prior to use to ensure compatibility.

DIRECTIONS FOR USE:

- Shake marker until you hear the agitator
- Twist the cap off
- Gently pump until the tip is primed

HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- Flash Point: 70°F (21.1°C)
- For complete health & safety data, refer to SDS at www.diagrammsp.com

TECH SPECS:

- Standard Stroke Width: 1/4"
- Fill Quantity: ~1 oz

PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	VOC Level	Resistant to	Total Halogens	Dry Time
Black	0971502	0.96	5.3 lbs/gal	650°F	< 64 ppm	20-30 Sec
Yellow	0971501	1.22	6.3 lbs/gal	650°F	50 ppm	20-30 Sec
White	0971500	1.22	5.6 lbs/gal	650°F	< 57 ppm	20-30 Sec
Blue	0971504	1.03	7.0 lbs/gal	650°F	< 24 ppm	20-30 Sec
Red	0971503	1.02	5.6 lbs/gal	650°F	< 200 ppm	20-30 Sec
Green	0971505	1.14	6.5 lbs/gal	650°F	42 ppm	20-30 Sec